



DOMESTIC HOT WATER TANKS WITH TWO INTEGRATED /
PARALLEL HEAT EXCHANGERS

EV 13S+17S 300 65

SAP Code	304892
Capacity	275 L
Net weight	112 kg
Insulation	50 mm
Heat exchanger surface S1	1.55 m ²
Heat exchanger surface S2	1.45 m ²
Heat exchanger capacity S1	9.5 L
Heat exchanger capacity S2	8.8 L
Heat losses ΔT 45K	68 W
Energy class	B
Maximum operational temperature	95 °C
Maximum operational temperature of the heat exchanger	110 °C



V40 - hot water delivered with a temperature of at least 40°C (S1)	382 L
V40 - hot water delivered with a temperature of at least 40°C (S2)	405 L
Diameter	650 mm



- Effectively heating full volume of water with two integrated heat exchangers with large surface.
- **HIGHLY EFFICIENT INSULATION CFC free PU foam** for minimal heat losses.
- High quality **ENAMEL COATING with TESY CrystalTech PRO** technology.
- **MAGNESIUM ANODES PROTECTION** of the inner tank surface for extended product life.
- Option for **INSTALLATION** of different power rated **HEATING ELEMENTS**.
- **SERVICE OPENING** for easy cleaning and maintenance.
- Recirculation opening.

Floor-standing indirectly heated water tanks with two integrated heat exchangers for production of domestic hot water. Heat exchangers are specially engineered to keep similar heat exchange surface to both of the serpentines.

The range includes models of 200, 300 and 500 L.

Advantages:

- Effectively heating full volume of water with two integrated heat exchangers with large surface.
- **HIGHLY EFFICIENT INSULATION CFC free PU foam** for minimal heat losses.
- High quality **ENAMEL COATING** with **TESY CrystalTech PRO** technology.
- **MAGNESIUM ANODES PROTECTION** of the inner tank surface for extended product life.
- Option for **INSTALLATION** of different power rated **HEATING ELEMENTS**.
- **SERVICE OPENING** for easy cleaning and maintenance.
- Recirculation opening.

*All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

The weights indicated in this website are net values for reference purposes only. Actual product weights may vary due to production tolerances.